

## Haiti DELIMAR

Item number 43295, KMAT 61000414




### Product description

DELIMAR fabrics have been specially developed for outdoor use. This upholstery fabric is made from the innovative Polyolefinic FR fiber, which permanently combines many positive properties. Flame retardancy, high light fastness, chlorine and seawater resistance and weather resistance are the hallmarks of this special fiber. The designs are machine-washable at 40°C and quick-drying, so that mold and bacteria cannot form in the first place. DELIMAR fabrics are free of harmful substances, antistatic and water-repellent. Haiti is a wonderfully textured plain that perfectly complements the patterned outdoor fabrics. Bold, clear colors are combined with white to radiate a fresh and summery mood.

DELIMAR fabrics should not be missing in the hotels and on the cruise ships of this world. With their memorable structures, they are an enrichment for the rooftop bar, the pool area, the outdoor lounge, the spa or the summer terrace. But they also create a special ambience indoors and offer great added value with their easy-care functions.

### Technical Details

<b>Fabric width</b>	approx. 140 cm
<b>Weight je m<sup>2</sup></b>	approx. 630 g/m <sup>2</sup>
<b>Composition</b>	100% Polyolefinic FR
<b>Flame retardancy</b>	IMO 2010 FTP Code Part 8, IMO 2010 FTP Code Part 7, 1 / M, BS 5852 CRIB 5, DIN EN 1021-2, DIN EN 1021-1, CAL TB 117, NFPA 260 Flammability performance is dependant on the foam used.
<b>Light fastness</b>	note 6

<b>Wash fastness 40°C</b> <b>DIN EN ISO 105-C06</b>	note 4-5
<b>Wash fastness 60°C</b> <b>DIN EN ISO 6330 DIN EN ISO 5077</b>	note 4-5
<b>Dimensional change Washing 40°C</b> <b>DIN EN ISO 6330 DIN EN ISO 5077</b>	warp approx. +/-2%, weft approx. +/-2%
<b>Dimensional change Washing 60°C</b> <b>DIN EN ISO 6330 DIN EN ISO 5077</b>	warp approx. +/-2%, weft approx. +/-3%
<b>Seawater safety</b> <b>DIN EN ISO 105-B02</b>	4-5
<b>Chlorine water safety</b>	4-5
<b>Rubbing fastness</b> <b>DIN EN ISO 105-X12</b>	dry: note 4-5, wet: note 4-5
<b>Abrasion to Martindale</b> <b>DIN EN ISO 12947-2</b> <b>DIN EN 14465-2006</b>	approx. 100000 rubs
<b>Pilling</b> <b>DIN EN ISO 12945-2</b>	Note 4 at 2000 rpm
<b>Care labelling</b>	
<b>Additional information</b>	<p>Bei dieser Ware handelt es sich um ein hochwertiges Gewebe aus Polyoefinic (Polypropylen). Unter künstlichem Licht neigen helle Farben zu leichten Verfärbungen. Dieses Phänomen ist technisch bedingt. Unter Sonneneinstrahlung verliert sich dieser Effekt.</p>
<b>State</b>	2024-04-23