



## Lennox DELIBLACK

Item number 41697, KMAT 61000391








### Product description

Blackouts have a blackout level of 100%. Thanks to a soft acrylic coating on the back, light rays cannot penetrate the material. The coating is particularly soft, which is why the fabric retains its flowing drape. All items in the Blackout range also have special stain protection and are naturally flame-retardant. With the use of melange yarns in the warp and weft and a brushed surface, Blackout Lennox has an incomparably soft wool character. The balanced color palette, consisting of seven colors, underlines the natural character.

### Technical Details

<b>Fabric width</b>	approx. 280 cm
<b>Weight je m²</b>	approx. 370 g/m²
<b>Composition</b>	100% Polyester Acrylat Softbeschichtung
<b>Flame retardancy</b>	IMO 2010 FTP Code Part 7, BS 5867 Typ B, EN 13773, DIN 4102 / B1, DIN 4102 / B2 Flammability performance is dependant on the foam used.
<b>Light fastness</b>	note 4-5
<b>Wash fastness 40°C DIN EN ISO 105-C06</b>	note 4-5
<b>Dimensional change Washing 40°C DIN EN ISO 6330 DIN EN ISO 5077</b>	warp approx. +/-2%, weft approx. +/-2%
<b>Rubbing fastness DIN EN ISO 105-X12</b>	dry: note 4-5, wet: note 4-5

Measured sound absorption coefficient DIN EN ISO 354/DIN EN ISO 11654	0.4
Sound absorption	Class D
Care labelling	    
Additional information	Nur die unbeschichtete Seite bügeln!
State	2024-04-09